MISCELLANEOUS APPARATUS

										MATERIAL					
INLET SIZES							2.5" OUTLET OPTIONS					DIMENSIONS			
Female	ale Male 2.5" Flan			lange											
2.5"	2.5"	3″	Ameri- can	Darley		Water- ous	Male NPT	Vic- taulic	NHT	Cast Brass	Elk-O Lite®	Length (Inches)	Weight (Lbs.)	MODEL	FIGURE
•							S			•		6.3	11.1	40-10	1
			•		•	•	S	0	0	•		6.8	11.2	40-20	1
				•			0	S		•		6.1	11.1	40-22	1
	тм						S			•		6.8	10.9	40-32	2
	•						S	0		•		6.5	10.6	40-40	2
		•					S	0		•		6.1	10.9	40-41	2
•							S				•	6.3	3.5	40A	

KEY s = standard o = option TM = NHT

40 RELIEF VALVE

- For use on the suction side of the pump or on a designated LDH discharge outlet
- Material: Choice of cast brass or Elk-O-Lite® with stainless steel mechanism
- · Rubber seat to ensure positive vacuum seal
- Adjustable psi of 75-250 (pre-set to 125 psi)



Figures depict general product types only and are not intended to be inclusive of all product features.

PUSH/PULL DRAIN VALVE



	MODELS						
Product Information	110	115					
Mounting	Direct	Panel					
Inlet	0.75" NPT Female						
Outlet	.75" NPT Female	Male shank outlet for .75" ID drain hose					
Handle length	2.25"						
Optional handle lengths	4.375", 3.0", or 1.5" (specify)						
Material	Cast brass valve body with stainless steel handle rod						
Additional features		Body pre-drilled for mounting					

116 QUARTER TURN DRAIN VALVE

- · Panel mounted
- Body pre-drilled for mounting to pump panel
- · Material: Cast brass valve body with stainless steel handle rod
- Inlet: 0.75" NPT
- Outlet: 0.75" NPT
- · Machined brass ball
- · Optional adapter with .125" NPT tap for gauge

