REMOTE VALVE CONTROLS

#### **TEE HANDLE REMOTE CONTROL UNITS**

Push-pull control for the operation of in-line, quarter turn ball valves or built-in eductors. Handle configuration allows identification/location label to be inserted.

	MODELS	
PRODUCT INFORMATION	RC-1	RC-7
Handle	Locking	Non-locking
Installation Diameter	1.9" (Pump panel)	1" (Pump panel)
Furnished with	2 ball joint swivel connector <b>s</b>	
Travel	11"	7.3", 9.8" or 11.3" (specify)
Material	Chrome-plated cast brass handle with anodized aluminum extrusion rod	
Weight	4 lbs.	1.5 lbs.



# de CY

#### REMOTE VALVE CONTROLS



#### RC-10 – SLOW CLOSING VALVE CONTROL

- · Remote actuation of any ball valve
- Linear output screw-type actuator compliant with NFPA 1901 (as it pertains to slow-closing valves)
- Actuator and push-rod constructed of extruded aluminum alloys
- · Precision needle thrust bearing and hardened thrust washers
- 5" cast alloy hand-wheel with collet-type connection allows for easy compact thru-panel installation (either new or retro-fit)
- · Furnished with threaded ball swivel joint at end of drive rod
- Installation diameter: 1.03" (pump panel)
- Length: 16.4" (retracted) and 21.4" (extended)
- · Weight: 3.2 lbs.
- Valve Status Indicator (optional)



#### **VALVE STATUS INDICATOR**

- · Requires minimal pump panel space
- Tri-color indicators: red (closed), yellow (gated) and green (open)
- Feature 100,000 hour ultra bright LEDs mounted within an optical filter to maximize visibility in bright sunlight
- · NEMA 4 rated
- · Chrome bezel included

## **RC** Accessories



#### **775-5 - HANDLE**

- For remote control screw type gate valve or gear driven valve
- · Bored for .375" rod
- · Material: Cast brass with chrome-plated finish
- · Diameter: 4"
- · Weight: 1.0 lbs.



#### 775-11 - ROD GUIDE

- · For centering and guiding remote control rod
- · Nylon sleeve for 0.5" rod
- · Material: Cast brass with chrome-plated finish
- Diameter: 1.5"
- · Weight: 0.2 lbs.



#### **775-15 - TEE HANDLE**

- For use with push-pull rods to remotely operate in-line, quarter turn ball valves or built-in eductors
- · Bored for 0.5" rod
- Can be threaded to .500" 13 or .500" 20 (specify)
- · Handle configuration allows identification/location label to be inserted
- · Material: Cast brass with chrome-plated finish
- Height: 1.1"
- · Weight: 0.5 lbs.

# **REMOTE VALVE CONTROLS**

# **UNIBODY HAND-WHEEL**

## **POSITION INDICATING**

	MODELS	
PRODUCT INFORMATION	GWP-4	GWP-6
Hand-wheel diameter	4"	6"
Material	Stainless Steel	
Finish	Stainless Steel	
Туре	Position Indicating	
Installation diameter	1.312"	
Weight	3.6 lbs.	4.1 lbs.





**GWP-4** 

**GWP-6** 

### **PANEL MOUNT**



	MODELS		
PRODUCT INFORMATION	GWR-5	GWR-6.5	
Hand-wheel diameter	5″	6.5"	
Material	Brass		
Finish (specify)	Chrome		
Туре	Panel Mount		
Installation diameter	1.125"		
Furnished with	Panel bushing and two universal		
rumsneu with	swivel joints with protective rubber boots		
Weight	6.0 lbs.	7.0 lbs.	

#### **DIRECT MOUNT**

	MODELS	
PRODUCT INFORMATION	GWD-5	GWD-6.5
Hand-wheel diameter	5″	6.5"
Material	Brass	
Finish (specify)	Chrome	
Туре	Direct Mount	
Installation diameter	-	
Furnished with	-	
Weight	6.0 lbs.	7.0 lbs.