

**Master Stream Nozzles for use with Monitors**

Inlet pressure and nozzle settings and the corresponding range and flow data is provided in the manufacturer's documentation.

**SM-1250BE-HLGM**

<b>Model</b>	<b>Nozzle Type</b>	<b>Construction Material</b>	<b>Inlet</b>	<b>Rated Operating Pressure, psi (bar)</b>	<b>Rated Flow Capacity, GPM (Lpm)</b>
SM-1250BE-HLGM	Constant Gallonage	Brass & Stainless Steel	3.5" NH Thread	72 (5.0)	1250 (4730)

This nozzle is rated as Suitable for use in Class I, Division 2, Groups A, B, C and D, T4 Hazardous (Classified) Locations for a maximum ambient of 140°F (60°C), and environment rating IP67 for the Motors and the Cables.

<b>Company Name:</b>	Elkhart Brass Mfg Co Inc
<b>Company Address:</b>	Box 1127, 1302 West Beardsley Ave, Elkhart, Indiana 46515, USA
<b>Company Website:</b>	<a href="http://www.elkhartbrass.com">http://www.elkhartbrass.com</a>
<b>New/Updated Product Listing:</b>	No
<b>Listing Country:</b>	United States of America
<b>Certification Type:</b>	FM Approved