



VISIT OUR WEBSITE FOR REPAIR VIDEOS  
[www.ElkhartBrass.com](http://www.ElkhartBrass.com)

\* FACTORY SERVICE ONLY COMPONENTS  
**DANGER: PARTS UNDER SPRING TENSION**

**ELKHART BRASS**  
 Fire Fighting Equipment

THIS DRAWING CONTAINS INFORMATION THAT IS PROPRIETARY TO ELKHART BRASS MFG CO., INC. AND MAY NOT BE USED TO PRODUCE ANY PARTS, ASSEMBLIES OR PRODUCTS DESCRIBED HEREIN WITHOUT EXPRESS WRITTEN PERMISSION

|   |                     |
|---|---------------------|
| SM XD MID LP-EXPLODED<br>(60-200@75)<br>PAGE 1 OF 2 | DRAWING<br>EXPLODED |
|---|---------------------|

| ITEM NO. | PART NUMBER | DESCRIPTION                                    | QTY. |
|----------|-------------|--|------|
| 1        | 16209007    | BODY - SHUTOFF (DD/DS)                         | 1    |
| 2        | 57324000    | O RING AS-568-140 2.237 X.103                  | 1    |
| 3        | 63863200    | SEAT-SHUTOFF                                   | 2    |
| 4        | 57309000    | O RING AS-568-224 1.734 X.139                  | 2    |
| 5        | 17341000    | BALL VALVE (1.375)                             | 1    |
| 6        | 65938000    | SHAFT - ACTUATOR                               | 2    |
| 7        | 57298000    | O RING AS-568-012 .364 X.070                   | 2    |
| 8        | 36697001    | HANDLE- BALE (FORGED)<br>GRAY HC               | 1    |
| 9        | 64005000    | SCREW - STOP                                   | 2    |
| 10       | 24680007    | COVER - ACTUATOR SHAFT                         | 2    |
| 11       | 57482000    | O RING AS-568-029 1.489 X.070                  | 2    |
| 12       | 64309000    | SCREW - 12-24 X 0.500<br>FLAT HD SOC CAP       | 2    |
| 13       | 59145507    | RING - RETAINING (TIP)                         | 1    |
| 14       | 65240000    | SCREW- 10-32x32 DG PT SS                       | 2    |
| 15       | 57577000    | O RING AS-568-224 1.734 X.139<br>90 DURO       | 1    |
| 16       | 16765007    | 1.5 F/S BASE<br>FOR 1.375 DIA WW SHUTOFFS      | 1    |
| 17       | 15018000    | 0.187 STAINLESS STEEL BALL                     | 32   |
| 18       | 63688000    | SCREW-SET (.375-24 X .25)<br>BLACK NYLON (6/6) | 1    |
| 19       | 33074000    | GASKET-RUBBER<br>2.062X1.562X.125TH            | 1    |
| 20       | 61269000    | SCREW 10-32X0.250 SOC SET<br>SS                | 1    |
| 21       | 391180XX    | INSERT - BALE HANDLE                           | 1    |
| 22       | 64162000    | SCREW - 4-40 X 0.250 SOC<br>CAP                | 4    |
| 23       | 33834007    | GRIP - PISTOL                                  | 1    |
| 24       | 64163000    | SCREW - 0.375-24 X 0.875 SOC<br>CAP            | 1    |
| 25       | 391170XX    | INSERT - PISTOL GRIP                           | 1    |
| 26       | 44789000    | LABEL- PRODUCT DATA                            | 1    |
| 27       | 18285007    | BODY (BASE) NOZZLE                             | 1    |

| ITEM NO. | PART NUMBER | DESCRIPTION                       | QTY. |
|----------|-------------|-----------------------------------|------|
| 28       | 11389007    | ADAPTER-SM XD                     | 1    |
| 29       | 61637001    | SLEEVE                            | 1    |
| 30       | 63392001    | STEM BASE WEB                     | 1    |
| 31       | 63579001    | SPACER                            | 1    |
| 32       | 47709000    | NUT HEX 0.312-24 NF SS            | 1    |
| 33       | 18131007    | BARREL-CENTER (MID)               | 1    |
| 34       | 338850XX    | GRIP - HAND (BUMPER)              | 1    |
| 35       | 58986001    | RING - TEETH (SPINNING)           | 1    |
| 36       | 59194000    | RING-WEAR                         | 1    |
| 37       | 66468507    | TIP - NOZZLE                      | 1    |
| 38       | 17236007    | BODY-TIP                          | 1    |
| 39       | 57638007    | RING-TEETH RETAINING              | 1    |
| 40       | 57334000    | O RING AS-568-133 1.799 X.103     | 1    |
| 41       | 57398000    | O RING AS-568-128 1.487 X.103     | 1    |
| 42       | 57420000    | O RING AS-568-134 1.862 X.103     | 1    |
| 43       | 57381000    | O RING AS-568-227 2.109 X.139     | 1    |
| 44       | 57422000    | O RING AS-568-033 1.989 X.070     | 1    |
| 45       | 58940000    | RING-RETAINING (EXTERNAL)         | 1    |
| 46       | 61780000    | SPRING-COIL                       | 1    |
| 47       | 71113000    | WASHER REINFORCING                | 1    |
| 48       | 69097007    | STEM SHAFT                        | 1    |
| 49       | 69096007    | STEM-HEAD                         | 1    |
| 50       | 33715000    | GUIDE - STEM                      | 1    |
| 51       | 64069000    | SCREW 4-40X0.750 SOC CAP<br>SS    | 3    |
| 52       | 57441000    | O RING AS-568-030 1.614 X.070     | 1    |
| 53       | 65209000    | SCREW 8-32X0.187 SOC<br>SETCUP SS | 1    |

**ELKHART BRASS**  
Fire Fighting Equipment

THIS DRAWING CONTAINS INFORMATION THAT IS PROPRIETARY TO ELKHART BRASS MFG CO., INC. AND MAY NOT BE USED TO PRODUCE ANY PARTS, ASSEMBLIES OR PRODUCTS DESCRIBED HEREIN WITHOUT EXPRESS WRITTEN PERMISSION

SM XD MID LP-EXPLODED  
PAGE 2 OF 2